

Inductance and Inductors

Disclaimer: These lecture notes are not meant to replace the course textbook. The content may be incomplete. Some topics may be unclear. These notes are only meant to be a study aid and a supplement to your own notes. Please report any inaccuracies to the professor.

Self Inductance

An inductor is a circuit element that stores magnetic field. If the magnetic field is changing, i.e. the current is changing, it will have an induced EMF across it with a magnitude proportional to the rate of change of current:

$$e = L \frac{di}{dt}$$

The proportionality constant L is called the inductance of the device. It is a property of the device (geometry, windings) and does not depend on the current. Inductance is measured in units of “henrys”, where 1 henry = 1 volt-second/ampere. For circuit analysis, it is enough to know just the inductance of the device and not the specific geometry.

As per Lenz’s Law, the sign of the EMF is determined such that it opposes the change in the magnetic flux through the device. When going from point “a” to point “b” on each end of the device, the EMF is given by:

$$e = DV = V_b - V_a = -L \frac{di}{dt}$$

So it increases in going from one end of the device to the other if the current is decreasing (and vice versa).

Note that by Faraday’s Law of Induction:

$$e = -N \frac{dF_B}{dt} = -L \frac{di}{dt} \quad N \text{ is the number of windings, } F_B \text{ is the flux through one winding}$$

$$\text{so } Li = NF_B$$

$$L = \frac{NF_B}{i}$$

Examples

Inductance of Solenoid

For a solenoid, $B = \mu_0 n i$ where n is the number of turns per unit length $n = \frac{N}{l}$.

$$e = -L \frac{di}{dt}$$

$$L = \frac{N \Phi_B}{i}$$

$$\diamond L = \frac{(nl)(\Phi_B)}{i} = \frac{(nl)(\mu_0 n i)(A)}{i} = \mu_0 n^2 A l$$

$$\boxed{L = \mu_0 n^2 V}$$

where V is the volume of the solenoid.

Inductance of a Toroid

For a toroid, $B = \frac{\mu_0 N i}{2\pi r}$

The magnetic field is perpendicular to the radius vector from the center of the circular toroid, thus it is parallel to the area vector through any radial slice across the toroid.

$$\Phi_B = \oint \mathbf{B} \cdot d\mathbf{A} = \oint B dA$$

$$\Phi_B = \oint B h dr \quad \text{where } h \text{ is the thickness of the toroid}$$

$$\Phi_B = \frac{\mu_0 N i}{2\pi} h \int \frac{dr}{r}$$

$$\Phi_B = \frac{\mu_0 N i}{2\pi} h \ln \frac{r_b}{r_a}$$

$$\boxed{L = \frac{N \Phi_B}{i} = \frac{\mu_0 N^2 h}{2\pi} \ln \frac{r_b}{r_a}}$$

Mutual Inductance

(to be filled in)

Energy Stored in an Inductor

Recall that the EMF is defined by $e = \frac{dW}{dq}$, the work done per unit charge by a source of EMF.

Power is $P = \frac{dW}{dt} = \frac{dW}{dq} \frac{dq}{dt} = ei$, and this is the power supplied by the source of EMF to maintain a current i .

This work applied by the EMF source is the negative of the work done by the magnetic field in setting up the EMF, and so this power directly changes the magnetic potential energy of the setup:

$$W = dU, \text{ so}$$

$$P = \frac{dU}{dt}$$

For a circuit containing only an inductor, this EMF is given by $e = L \frac{di}{dt}$, so

$$P = Li \frac{di}{dt} = \frac{dU}{dt}$$

$$\diamond dU = Lidi$$

$$\diamond U = \int Lidi$$

$$U = \frac{1}{2} Li^2$$

This is the magnetic potential energy stored in an inductor. Contrast this to the electric potential energy stored in a capacitor: $U = \frac{1}{2} C (DV)^2 = \frac{q^2}{2C}$

Energy Density of a Magnetic Field

Take the specific case of a solenoid:

$$L = \mu_0 n^2 V, \text{ so}$$

$$U = \frac{1}{2} \mu_0 n^2 V i^2 = \frac{B^2}{2\mu_0} V$$

The energy density (energy per unit volume) can be defined as:

$$u = \frac{U}{V} = \frac{B^2}{2\mu_0}$$