

CMSC 330: Organization of Programming Languages

Examples of REs & Finite Automata

Describing Regular Expressions

- a) $0(0|1)^*0$
 - All strings beginning and ending in 0
- b) $((\epsilon | 0)1^*)^*$
 - All strings
- c) $(0|1)^*0(0|1)(0|1)$
 - All strings with 0 as third digit from right

CMSC 330

2

Creating Regular Expressions

For all strings of 0's and 1's that...





- a) Begin in 1
 - $1(0|1)^*$
- b) End in 1
 - $(0|1)^*1$
- c) Contains 00
 - $(0|1)^*00(0|1)^*$
- d) Do not contain 00
 - $(0|1|1)^*(\epsilon | 0)$

CMSC 330

3

Creating NFA

For all strings of 0's and 1's that...

- a) Begin in 1
 
- b) End in 1
 
- c) Contains 00
 
- d) Do not contain 00
 





Based on regular expression

CMSC 330

4

Creating DFA


For all strings of 0's and 1's that...

- a) Begin in 1
 
 - b) End in 1
 
 - c) Contains 00
 
 - d) Do not contain 00
 
- Swap final / non-final states!

CMSC 330

5

For RE $(a | b)^*$

- a) Construct NFA
 
- b) Accept ababbab
 - 7,5,1,2,6,8,7,5,3,4,6,8,7,5,1,2,6,8,7,5,3,4,6,8,7,5,3,4,6,8,7,5,1,2,6,8,7,5,3,4,6,8 accept

CMSC 330

6

For RE $(a | b)^*$

c) Reduce NFA to DFA

- Start = ϵ -closure(7) = {7,5,1,3,8}
- $R = \{\{7,5,1,3,8\}\}$
- $r \in R = \{7,5,1,3,8\}$ // mark DFA state
- move ($\{7,5,1,3,8\}, a$) = {2}
 - $e = \epsilon$ -closure({2}) = {2,6,8,7,5,1,3} // new DFA state
 - $R = R \cup \{2,6,8,7,5,1,3\}$ // add to R
 - $\delta = \delta \cup (\{7,5,1,3,8\}, a, \{2,6,8,7,5,1,3\})$
- move ($\{7,5,1,3,8\}, b$) = {4}
 - $e = \epsilon$ -closure({4}) = {4,6,8,7,5,1,3} // new DFA state
 - $R = R \cup \{4,6,8,7,5,1,3\}$ // add to R
 - $\delta = \delta \cup (\{7,5,1,3,8\}, b, \{4,6,8,7,5,1,3\})$

CMSC 330

7

For RE $(a | b)^*$

- $R = \{\{7,5,1,3,8\}, \{2,6,8,7,5,1,3\}, \{4,6,8,7,5,1,3\}\}$
- $r \in R = \{2,6,8,7,5,1,3\}$ // mark DFA state
- move ($\{2,6,8,7,5,1,3\}, a$) = {2}
 - $e = \epsilon$ -closure({2}) = {2,6,8,7,5,1,3} // existing DFA state
 - $\delta = \delta \cup (\{2,6,8,7,5,1,3\}, a, \{2,6,8,7,5,1,3\})$
- move ($\{2,6,8,7,5,1,3\}, b$) = {4}
 - $e = \epsilon$ -closure({4}) = {4,6,8,7,5,1,3} // existing DFA state
 - $\delta = \delta \cup (\{2,6,8,7,5,1,3\}, b, \{4,6,8,7,5,1,3\})$

CMSC 330

8

For RE $(a | b)^*$

- $R = \{\{7,5,1,3,8\}, \{2,6,8,7,5,1,3\}, \{4,6,8,7,5,1,3\}\}$
- $r \in R = \{4,6,8,7,5,1,3\}$ // mark DFA state
- move ($\{4,6,8,7,5,1,3\}, a$) = {2}
 - $e = \epsilon$ -closure({2}) = {2,6,8,7,5,1,3} // existing DFA state
 - $\delta = \delta \cup (\{4,6,8,7,5,1,3\}, a, \{2,6,8,7,5,1,3\})$
- move ($\{4,6,8,7,5,1,3\}, b$) = {4}
 - $e = \epsilon$ -closure({4}) = {4,6,8,7,5,1,3} // existing DFA state
 - $\delta = \delta \cup (\{4,6,8,7,5,1,3\}, b, \{4,6,8,7,5,1,3\})$
- $R = \{\{7,5,1,3,8\}, \{2,6,8,7,5,1,3\}, \{4,6,8,7,5,1,3\}\}$
 - No more unmarked states to process
- $F_d = \{\{7,5,1,3,8\}, \{2,6,8,7,5,1,3\}, \{4,6,8,7,5,1,3\}\}$
 - Since $\delta \in F_d$

CMSC 330

9

For RE $(a | b)^*$


- Resulting DFA
 - $\Sigma = \{a,b\}$
 - $R = \{\{7,5,1,3,8\}, \{2,6,8,7,5,1,3\}, \{4,6,8,7,5,1,3\}\}$
 - $r_0 = \{7,5,1,3,8\}$
 - $F_d = \{\{7,5,1,3,8\}, \{2,6,8,7,5,1,3\}, \{4,6,8,7,5,1,3\}\}$
 - $\delta = \{$
 - $(\{7,5,1,3,8\}, a, \{2,6,8,7,5,1,3\}),$
 - $(\{7,5,1,3,8\}, b, \{4,6,8,7,5,1,3\}),$
 - $(\{2,6,8,7,5,1,3\}, a, \{2,6,8,7,5,1,3\}),$
 - $(\{2,6,8,7,5,1,3\}, b, \{4,6,8,7,5,1,3\}),$
 - $(\{4,6,8,7,5,1,3\}, a, \{2,6,8,7,5,1,3\}),$
 - $(\{4,6,8,7,5,1,3\}, b, \{4,6,8,7,5,1,3\})$

CMSC 330

10

For RE $(a | b)^*$

- NFA to DFA reduction pictorial




CMSC 330

11

For RE $(a | b)^*$

d) Minimize DFA

- Initial partitions
 - Accept $\rightarrow \{1,2,3\} = P1$
 - Reject $\rightarrow \emptyset$
- Split partition?
 - move(1,a) $\rightarrow P1$
 - move(2,a) $\rightarrow P1$
 - move(3,a) $\rightarrow P1$
 - move(1,b) $\rightarrow P1$
 - move(2,b) $\rightarrow P1$
 - move(3,b) $\rightarrow P1$




Not required, minimization done

CMSC 330

12

For RE $(a^* | b^*)^*$

a) Construct NFA



b) Accept ababbab

11,9,3,1,2,4,10,12,11,9,7,5,6,8,10,12,11,9,3,1,2,4,10,12...


CMSC 330

13

For RE $(a^* | b^*)^*$

c) Reduce NFA to DFA

- Start = ϵ -closure(1) = {11,9,3,1,4,7,5,8,10,12}
- $R = \{\{11,9, \dots, 12\}\}$
- $r \in R = \{11,9, \dots, 12\}$
 - move ($\{11,9, \dots, 12\}, a$) = 2
 - ϵ -closure($\{2\}$) = {2,11,9, \dots, 12}
 - move ($\{11,9, \dots, 12\}, b$) = 6
 - ϵ -closure($\{6\}$) = {6,11,9, \dots, 12}
 - ...
- NFA to DFA reduction pictorial




CMSC 330

14

For RE $(a^* | b^*)^*$

d) Minimize DFA

- Initial partitions
 - Accept - {1,2,3} - P1
 - Reject - \emptyset
- Split partition?
 - move(1,a) - P1
 - ...
- Not required, minimization done



e) Compare 2 minimized DFAs

- Identical up to state names!

CMSC 330

15